

Mitraset Racklite Basic 19"

housing

Housing for electronic instruments

Product description

- Designed to hold electronic equipment in a 19" grid in accordance with VG 95446
- Variable designs with different depths and heights.
- Comprehensive range of special fittings for many applications.
- Protection rating IP 65 in accordance with DIN EN 60529 and IEC 34-5/529 as a result of welded casing and lid with all-round seal.
- The anti-vibration frame is connected to the housing via 8 rubber dampers and 2 earth straps.
- Stackable using stacking knobs and recesses.
- Items with same nominal depth are stackable.
- ZARGES Comfort handles for ergonomic handling and loads of up to 50 kg.
- ZARGES Comfort fastener for ergonomic operation and an extremely long service life.
- Snap fasteners with protection against bursting open.
- RF-tight version is available as special equipment.



Product variants

Order number	Installation height	Nominal depth	Outside dimensions L x W x H	Weight
45943	3 HE/U	350 mm	456 mm × 568 mm × 226 mm	7.7 kg
45944	4 HE/U	350 mm	456 mm × 568 mm × 270,5 mm	8.3 kg
45945	5 HE/U	350 mm	456 mm × 568 mm × 315 mm	8.7 kg
45946	6 HE/U	350 mm	456 mm × 568 mm × 359,5 mm	9 kg
45947	7 HE/U	350 mm	456 mm × 568 mm × 404 mm	9.3 kg
45948	8 HE/U	350 mm	456 mm × 568 mm × 448,5 mm	9.6 kg
45949	9 HE/U	350 mm	456 mm × 568 mm × 493 mm	10 kg
45950	10 HE/U	350 mm	456 mm × 568 mm × 537,5 mm	10.3 kg
45951	11 HE/U	350 mm	456 mm × 568 mm × 582 mm	10.6 kg
45952	12 HE/U	350 mm	456 mm × 568 mm × 626,5 mm	11 kg
45953	3 HE/U	480 mm	586 mm × 568 mm × 226 mm	9.1 kg
45954	4 HE/U	480 mm	586 mm × 568 mm × 270,5 mm	9.8 kg
45955	5 HE/U	480 mm	586 mm × 568 mm × 315 mm	10.2 kg
45956	6 HE/U	480 mm	586 mm × 568 mm × 359,5 mm	10.5 kg
45957	7 HE/U	480 mm	586 mm × 568 mm × 404 mm	10.5 kg
45958	8 HE/U	480 mm	586 mm × 568 mm × 448,5 mm	11.3 kg
45959	9 HE/U	480 mm	586 mm × 568 mm × 493 mm	11.7 kg
45960	10 HE/U	480 mm	586 mm × 568 mm × 537,5 mm	12 kg
45961	11 HE/U	480 mm	586 mm × 568 mm × 582 mm	12.4 kg
45962	12 HE/U	480 mm	586 mm × 568 mm × 626,5 mm	12.8 kg

Order number	Installation height	Nominal depth	Outside dimensions L x W x H	Weight
45963	3 HE/U	610 mm	716 mm × 568 mm × 226 mm	10.4 kg
45964	4 HE/U	610 mm	716 mm × 568 mm × 270,5 mm	11.1 kg
45965	5 HE/U	610 mm	716 mm × 568 mm × 315 mm	11.5 kg
45966	6 HE/U	610 mm	716 mm × 568 mm × 359,5 mm	11.9 kg
45967	7 HE/U	610 mm	716 mm × 568 mm × 404 mm	12.3 kg
45968	8 HE/U	610 mm	716 mm × 568 mm × 448,5 mm	12.8 kg
45969	9 HE/U	610 mm	716 mm × 568 mm × 493 mm	13.2 kg
45970	10 HE/U	610 mm	716 mm × 568 mm × 537,5 mm	13.6 kg
45971	11 HE/U	610 mm	716 mm × 568 mm × 582 mm	14 kg
45972	12 HE/U	610 mm	716 mm × 568 mm × 626,5 mm	14.4 kg
45973			x x	
45974			x x	
45975			x x	
45976			x x	
45977			x x	
45978			x x	
45979			x x	
45980			x x	
45981			x x	
45982			x x	