


Mobile access steps with platform

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Cantilever platform available for bridging obstacles.
- Chassis available in a non-static version as an option.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product features

Warranty: 10 years

Product variants

Order number	Chassis width	Inclination	Number of treads	Overall span	Tread width	Vertical height
40255764	1020 mm	45 °	5	1698 mm	600 mm	1070 mm
40255766	1620 mm	45 °	7	2128 mm	600 mm	1500 mm
40255768	1620 mm	45 °	9	2558 mm	600 mm	1930 mm
40255770	1220 mm	45 °	11	3017 mm	600 mm	2360 mm
40255772	1220 mm	45 °	12	3447 mm	600 mm	2790 mm
40255774	1220 mm	45 °	14	3877 mm	600 mm	3220 mm
40255776	1220 mm	45 °	16	4307 mm	600 mm	3650 mm
40255778	1420 mm	45 °	18	4737 mm	600 mm	4080 mm
40255780	1420 mm	45 °	20	5167 mm	600 mm	4510 mm
40255784	1020 mm	45 °	5	1698 mm	800 mm	1070 mm



Order number	Chassis width	Inclination	Number of treads	Overall span	Tread width	Vertical height
40255786	1220 mm	45 °	7	2128 mm	800 mm	1500 mm
40255788	1220 mm	45 °	9	2558 mm	800 mm	1930 mm
40255790	1220 mm	45 °	11	3017 mm	800 mm	2360 mm
40255792	1220 mm	45 °	12	3447 mm	800 mm	2790 mm
40255794	1420 mm	45 °	14	3877 mm	800 mm	3220 mm
40255796	1420 mm	45 °	16	4307 mm	800 mm	3650 mm
40255798	1420 mm	45 °	18	4737 mm	800 mm	4080 mm
40255800	1620 mm	45 °	20	5167 mm	800 mm	4510 mm
40255804	1420 mm	45 °	5	1698 mm	1000 mm	1070 mm
40255806	1420 mm	45 °	7	2128 mm	1000 mm	1500 mm
40255808	1420 mm	45 °	9	2558 mm	1000 mm	1930 mm
40255810	1420 mm	45 °	11	3017 mm	1000 mm	2360 mm
40255812	1420 mm	45 °	12	3447 mm	1000 mm	2790 mm
40255814	1420 mm	45 °	14	3877 mm	1000 mm	3220 mm
40255816	1420 mm	45 °	16	4307 mm	1000 mm	3650 mm
40255818	1420 mm	45 °	18	4737 mm	1000 mm	4080 mm
40255820	1620 mm	45 °	20	5167 mm	1000 mm	4510 mm
40255704	1220 mm	60 °	5	1453 mm	600 mm	1250 mm
40255706	1420 mm	60 °	7	1707 mm	600 mm	1750 mm
40255708	1820 mm	60 °	9	1996 mm	600 mm	2250 mm
40255710	1620 mm	60 °	11	2285 mm	600 mm	2750 mm
40255712	1620 mm	60 °	12	2607 mm	600 mm	3250 mm
40255714	1620 mm	60 °	14	2896 mm	600 mm	3750 mm
40255716	1620 mm	60 °	17	3185 mm	600 mm	4250 mm
40255724	1220 mm	60 °	5	1453 mm	800 mm	1250 mm
40255726	1220 mm	60 °	7	1707 mm	800 mm	1750 mm
40255728	1620 mm	60 °	9	1996 mm	800 mm	2250 mm
40255730	1420 mm	60 °	11	2285 mm	800 mm	2750 mm
40255732	1420 mm	60 °	12	2607 mm	800 mm	3250 mm
40255734	1420 mm	60 °	14	2896 mm	800 mm	3750 mm
40255736	1620 mm	60 °	17	3185 mm	800 mm	4250 mm
40255744	1420 mm	60 °	5	1453 mm	1000 mm	1250 mm
40255746	1420 mm	60 °	7	1707 mm	1000 mm	1750 mm
40255748	1420 mm	60 °	9	1996 mm	1000 mm	2250 mm
40255750	1420 mm	60 °	11	2285 mm	1000 mm	2750 mm
40255752	1420 mm	60 °	12	2607 mm	1000 mm	3250 mm
40255754	1420 mm	60 °	14	2720 mm	1000 mm	3750 mm
40255756	1620 mm	60 °	17	3207 mm	1000 mm	4250 mm