

Access steps with platform

Stationary access to buildings and machines with platforms.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Support section mounting element for use as a free-standing work platform.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.
Standard applied: DIN EN ISO 14122.

Product features

Load capacity: max. 300 kg
Platform length: 600 mm
Standards: EN ISO 14122
Warranty: 10 years
load-capacity-step-td: 150 kg

Product variants

Order number	Inclination	Number of treads	Overall span	Tread width	Vertical height
40155424	45 °	5	1730 mm	600 mm	1070 mm
40155426	45 °	7	2160 mm	600 mm	1500 mm
40155428	45 °	9	2590 mm	600 mm	1930 mm
40155430	45 °	11	3020 mm	600 mm	2360 mm
40155432	45 °	13	3451 mm	600 mm	2790 mm
40155434	45 °	15	3881 mm	600 mm	3220 mm
40155436	45 °	17	4311 mm	600 mm	3650 mm
40155438	45 °	19	4741 mm	600 mm	4080 mm
40155444	45 °	5	1730 mm	800 mm	1070 mm
40155446	45 °	7	2160 mm	800 mm	1500 mm
40155448	45 °	9	2590 mm	800 mm	1930 mm



Order number	Inclination	Number of treads	Overall span	Tread width	Vertical height
40155450	45 °	11	3020 mm	800 mm	2360 mm
40155452	45 °	13	3451 mm	800 mm	2790 mm
40155454	45 °	15	3881 mm	800 mm	3220 mm
40155456	45 °	17	4311 mm	800 mm	3650 mm
40155458	45 °	19	4741 mm	800 mm	4080 mm
40155464	45 °	5	1730 mm	1000 mm	1070 mm
40155466	45 °	7	2160 mm	1000 mm	1500 mm
40155468	45 °	9	2590 mm	1000 mm	1930 mm
40155470	45 °	11	3020 mm	1000 mm	2360 mm
40155472	45 °	13	3451 mm	1000 mm	2790 mm
40155474	45 °	15	3881 mm	1000 mm	3220 mm
40155476	45 °	17	4311 mm	1000 mm	3650 mm
40155478	45 °	19	4741 mm	1000 mm	4080 mm
40155364	60 °	5	1407 mm	600 mm	1250 mm
40155366	60 °	7	1695 mm	600 mm	1750 mm
40155368	60 °	9	1984 mm	600 mm	2250 mm
40155370	60 °	11	2273 mm	600 mm	2750 mm
40155372	60 °	13	2561 mm	600 mm	3250 mm
40155374	60 °	15	2850 mm	600 mm	3750 mm
40155376	60 °	17	3139 mm	600 mm	4250 mm
40155378	60 °	19	3427 mm	600 mm	4750 mm
40155384	60 °	5	1407 mm	800 mm	1250 mm
40155386	60 °	7	1695 mm	800 mm	1750 mm
40155388	60 °	9	1984 mm	800 mm	2250 mm
40155390	60 °	11	2273 mm	800 mm	2750 mm
40155392	60 °	13	2561 mm	800 mm	3250 mm
40155394	60 °	15	2850 mm	800 mm	3750 mm
40155396	60 °	17	3139 mm	800 mm	4250 mm
40155398	60 °	19	3427 mm	800 mm	4750 mm
40155404	60 °	5	1407 mm	1000 mm	1250 mm
40155406	60 °	7	1695 mm	1000 mm	1750 mm
40155408	60 °	9	1984 mm	1000 mm	2250 mm
40155410	60 °	11	2273 mm	1000 mm	2750 mm
40155412	60 °	13	2561 mm	1000 mm	3250 mm
40155414	60 °	15	2850 mm	1000 mm	3750 mm
40155416	60 °	17	3139 mm	1000 mm	4250 mm
40155418	60 °	19	3427 mm	1000 mm	4750 mm