


Compact work platform with easy-going steps. Choice of stationary or mobile version (for moving quickly to another working position). Ideal for work over long periods, even with tools.

- Individually adjustable platform lengths.
- Chassis available in a non-static version as an option.
- Configurable up to a vertical height of 1,500 mm (from 1,000 mm with horizontal stabiliser bar for safe standing).
- Assembly elements: Support section assembly elements selectable without wheel or as a stationary work platform with floor brackets.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



Inclination: 45 °  
Load capacity: max. 300 kg  
Number of treads: 4  
Overall span: 1351 mm  
Platform length: 400 mm  
Standards: EN ISO 14122  
Tread width: 600 mm  
Vertical height: 800 mm  
Warranty: 10 years  
load-capacity-step-td: 150 kg

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.  
Standard applied: DIN EN ISO 14122.

Image	Order number	Name	Type
-------	--------------	------	------