

Reachmaster S-PLUS 1T

The economical folding scaffold unit with advanced guardrail and two metre platform distance.

Product description

- Scaffolding width: 0.68 m; scaffolding length: 1.80 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights can be extended from 4.55 m to max. 9.85 m with standard parts.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: 125 mm with pin (no height adjustment) and rubber coating, for working heights of up to 6.55m.



Product features

Length as work platform: 1.8 m
 Platform size: 0,6m × 1,8m
 Platform width: 0.6 m

Product variants

Order number	Overall height	Platform height	Weight	Working height
53743	3.9 m	2.55 m	75.9 kg	4.55 m
53744	5 m	3.7 m	127.7 kg	5.7 m
53745	5.85 m	4.55 m	132.3 kg	6.55 m
53746	7.15 m	5.85 m	183.1 kg	7.85 m
53747	8.05 m	6.7 m	190 kg	8.7 m
53748	8.9 m	7.85 m	223.9 kg	9.85 m
53749	9.65 m	8.65 m	245 kg	10.65 m