

Stationary bridging steps - 40355923

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.

Product features

Clear height, stationary: 880 mm
 Inclination: 60 °
 Load capacity: max. 300 kg
 Number of treads: 4
 Overall span: 1915 mm
 Platform length: 600 mm
 Standards: EN ISO 14122
 Tread width: 1000 mm
 Warranty: 10 years
 load-capacity-step-td: 150 kg



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.
 Standard applied: DIN EN ISO 14122.

Accessories and spare parts

Image	Order number	Name	Type
	41967	Tray	Accessory