

Everest 3DE

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Overall width of bottom section: 490 mm.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Ext. width: 490 mm
 External width of lower ladder: 490 mm
 Load: max. 150 kg
 Material: Aluminium
 Number ladderparts: 3
 Pitch rung/tread: 265 mm
 Producttype: Flanged push-up ladder with rungs, 3-section
 Tread depth: 38 mm
 Type rung/tread: serrated

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece	Working height
44851	8	3 × 8	5.25 m	2.41 m	2.410 mm × 500 mm × 170 mm	15.3 kg	0.9 m	5.95 m
44852	10	3 × 10	6.65 m	2.97 m	2.970 mm × 500 mm × 190 mm	19.2 kg	1.1 m	7.25 m
44853	12	3 × 12	8.33 m	3.53 m	3.530 mm × 500 mm × 190 mm	24.2 kg	1.2 m	8.8 m
44854	14	3 × 14	9.45 m	4.09 m	4.090 mm × 500 mm × 190 mm	36 kg	1.2 m	9.9 m