

Coni B - 40274

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Product features

Anti splay: Belt strap
 Base: 0,9 m × 0,47 m
 Coating: natural
 Connection Stile-Rung: flanged
 Load capacity: max. 150 kg
 Material: Aluminium
 Number of rungs: 4
 Number of rungs: 2 × 4
 Overall base width: 0.47 m
 Overall length: 1.22 m
 Pitch rung/tread: 265 mm
 Standards: EN 131 professional
 Stile depth: 50 mm
 Transport dimensions: 1.220 mm × 470 mm × 140 mm
 Tread depth: 30 mm
 Type rung/tread: serrated
 Vertical ladder height: 1.2 m
 Warranty: 10 years
 Weight: 4.4 kg
 Working height: 2.5 m

Hints and special features

Stepladder for maximum working heights of up to 6.70 m.
 Complies with EN 131 Professional.

Accessories and spare parts

Image	Order number	Name	Type
	824347	Plug-in end cap	Spare part
	824160	End cap	Spare part



Image	Order number	Name	Type
	820816	Bracing	Spare part
	809021	Hinge	Spare part
	829729	Splay prevention (belt strap)	Spare part