

## Coni B - 40277

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

### Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Product features

Anti splay: Belt strap  
 Base: 1,41 m × 0,57 m  
 Coating: natural  
 Connection Stile-Rung: flanged  
 Load capacity: max. 150 kg  
 Material: Aluminium  
 Number of rungs: 7  
 Number of rungs: 2 × 7  
 Overall base width: 0.57 m  
 Overall length: 2.06 m  
 Pitch rung/tread: 265 mm  
 Standards: EN 131 professional  
 Stile depth: 58 mm  
 Transport dimensions: 2.080 mm × 570 mm × 155 mm  
 Tread depth: 30 mm  
 Type rung/tread: serrated  
 Vertical ladder height: 1.99 m  
 Warranty: 10 years  
 Weight: 7.3 kg  
 Working height: 3.25 m

### Hints and special features

Stepladder for maximum working heights of up to 6.70 m.  
 Complies with EN 131 Professional.

### Accessories and spare parts

Image	Order number	Name	Type
	824350	Plug-in end cap	Spare part
	824152	End cap	Spare part



Image	Order number	Name	Type
	820816	Bracing	Spare part
	809021	Hinge	Spare part
	827675	Splay prevention (belt strap)	Spare part