

# PaxTower S-PLUS 1T - 53521

With advanced guardrail for extra safety and compliance with the new EN 1004:2020

## Product description

- Safer and quicker assembly and dismantling due to advanced guardrails and platforms at intervals of 2 m.
- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m<sup>2</sup>) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42974) to allow for height adjustment.
- Stile and rung diameter 45 mm.



## Product features

Claw type: automatic  
 Fits through doorways: Yes  
 Height-adjustable castors: No  
 Overall height: 1.65 m  
 Platform height: 0.55 m  
 Platform length: 1.8 m  
 Platform width: 0.6 m  
 Platform size: 0,6m × 1,8m  
 Rung diameter: 45 mm  
 Scaffolding class: 3 (= 200 kg/m<sup>2</sup>)  
 Standards: EN 1004-1  
 Stile diameter: 45 mm  
 Transport dimensions: 1.950 mm × 750 mm × 400 mm  
 Warranty: 10 years  
 Weight: 38.3 kg  
 Wheel diameter: 125 mm  
 Width scaffolding: 0.72 m  
 Working height: 2.55 m