

PaxTower S-PLUS 1T - 53524

With advanced guardrail for extra safety and compliance with the new EN 1004:2020

Product description

- Safer and quicker assembly and dismantling due to advanced guardrails and platforms at intervals of 2 m.
- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42974) to allow for height adjustment.
- Stile and rung diameter 45 mm.



Product features

Claw type: automatic
 Fits through doorways: Yes
 Height-adjustable castors: No
 Overall height: 4.65 m
 Platform height: 3.55 m
 Platform length: 1.8 m
 Platform width: 0.6 m
 Platform size: 0,6m × 1,8m
 Rung diameter: 45 mm
 Scaffolding class: 3 (= 200 kg/m²)
 Standards: EN 1004-1
 Stile diameter: 45 mm
 Transport dimensions: 2.150 mm × 750 mm × 950 mm
 Warranty: 10 years
 Weight: 108 kg
 Wheel diameter: 125 mm
 Width scaffolding: 0.72 m
 Working height: 5.55 m