

Everest Plus 2E - 40468

Better footing at the top. The push-up ladder with 80 mm deep treads instead of rungs.

Product description

- Provides a safe place to stand for work at height. The push-up ladder with treads instead of rungs.
- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- The upper ladder is fitted with plastic wheels to prevent damage to walls.
- Height adjustment in increments of 280 mm.
- Upper ladder fitted with plastic wall wheels.
- · Locks safely by means of hooks with lift-off retainer.
- Ladder width: 420 mm.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Coating: natural

Connection Stile-Rung: flanged

External width of lower ladder: 420 mm

Load capacity: max. 150 kg Material: Aluminium

Number of rungs: 10 Number of rungs: 2 × 10

Overall length, extended: 5.32 m Overall length, retracted: 3.08 m

Pitch rung/tread: 265 mm Standards: EN 131 professional

Stile depth: 73 mm

Transport dimensions: approx. 3.080 mm × approx. 420

mm × approx. 200 mm Warranty: 10 years Weight: 13.9 kg Wheels: Rubber Wide crosspiece: 1 m Working height: 5.95 m



Hints and special features

Complies with EN 131 Professional.

Accessories and spare parts

Image	Order number	Name	Туре
	40300	Toolbag	Accessory
	40998	Ladder holder, lockable	Accessory

ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-0 Fax: +49 (0)881-687-0 www.zarges.com internationalsales@zarges.de



Image	Order number	Name	Туре
-	40960	Tension strap	Accessory
	40058	Hanging hooks	Accessory
	40059	Hanging hooks	Accessory
	40213	Clamp-on stile extension	Accessory
	40939	Ground spikes	Parts list
	41989	Stile extension for horizontal stabiliser bars	Parts list
	824352	Plug-in end cap	Spare part
	824243	Push-on end cap	Spare part
	824153	End cap	Spare part
	824369	Inclination-angle indicator	Spare part
	800542	Horizontal stabiliser bar	Spare part
	800530	Safer Step tread inset	Spare part